

Printed on 14/12/2022
Page n. 1 / 13
Replaced revision:3 (Dated 22/10/2020)

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

CEMENTO MATERICO Product name

UFI: RH00-Y0PM-U00U-MH1W

1.2. Relevant identified uses of the substance or mixture and uses advised against

Water based decorative paint based on lime. Professional and home use. Intended use

Uses advised against Uses other than those indicated

1.3. Details of the supplier of the safety data sheet

Name **OIKOS S.P.A. A SOCIO UNICO**

Full address Via Cherubini 2

(FC) District and Country 47043 **Gatteo Mare**

Italia

Tel. 0547 681412 0547 681430 Fax

e-mail address of the competent person

certificazioniprodotti@oikos-group.it responsible for the Safety Data Sheet

1.4. Emergency telephone number

For urgent inquiries refer to **NHS National Health Service 111**

OIKOS S.P.A. a socio unico Company emergency number: 0547 681412 Technical support - Monday to Friday from 8.00-13.00; 13:30 to 16:30

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1 H318 Causes serious eye damage. Skin irritation, category 2 H315 Causes skin irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H318 Causes serious eye damage. H315 Causes skin irritation.



Revision nr.4 Dated 12/12/2022 Printed on 14/12/2022
Page n. 2 / 13
Replaced revision:3 (Dated 22/10/2020)

.../>> **SECTION 2. Hazards identification**

> **EUH208** Contains: Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one[EC no. 247-500-7] and

> > 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

1,2-benzisothiazol-3(2H)-one

May produce an allergic reaction.

Precautionary statements:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P501 Dispose of contents / container in accordance with local regulation.

P102 Keep out of reach of children.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

Immediately call a POISON CENTER / doctor / . . P310

P101 If medical advice is needed, have product container or label at hand.

P302+P352 IF ON SKIN: wash with plenty of water / . . .

Contains: Calcium dihydroxide

VOC (Directive 2004/42/EC):

Decorative effect coatings.

VOC given in g/litre of product in a ready-to-use condition : 8,00 Limit value: 200,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

Calcium dihydroxide

 $15 \le x < 20$ Eve Dam. 1 H318, Skin Irrit, 2 H315, STOT SE 3 H335 INDEX

EC 215-137-3 CAS 1305-62-0 REACH Reg. 01-2119475151-45 C12-C15 propoxylated alcohol

INDEX $0.5 \le x < 1.5$ Acute Tox. 4 H302 933-043-7 STA Oral: 500 mg/kg FC

CAS 74499-34-6 1.2-benzisothiazol-3(2H)-one

INDEX 613-088-00-6 $0.0057 \le x < 0.0068$ Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315,

Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411

220-120-9 Skin Sens. 1 H317: ≥ 0,05% EC

2634-33-5 LD50 Oral: >490 mg/kg bw, STA Inhalation mists/powders: 0,051 mg/l, STA CAS

Inhalation vapours: 0,501 mg/l

REACH Reg. 01-2120761540-60

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one[EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]

(3:1)

INDEX 613-167-00-5 Acute Tox. 1 H330, Acute Tox. 2 H310, Acute Tox. 3 H301, Skin Corr. 1B $0,0005 \le x < 0,00144$

H314, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=100,

Aquatic Chronic 1 H410 M=100

FC. 611-341-5 Skin Corr. 1C H314: ≥ 0,6%, Skin Irrit. 2 H315: ≥ 0,06%, Skin Sens. 1 H317: ≥

0,0015%, Eye Irrit. 2 H319: ≥ 0,6%

55965-84-9 LD50 Oral: >64 mg/kg bw, STA Dermal: 50,001 mg/kg, STA Inhalation CAS

vapours: 0,05 mg/l

01-2120764691-48 REACH Reg.

The full wording of hazard (H) phrases is given in section 16 of the sheet.



Revision nr.4 Dated 12/12/2022 Printed on 14/12/2022 Page n. 3 / 13 Replaced revision:3 (Dated 22/10/2020)

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.



Revision nr.4
Dated 12/12/2022
Printed on 14/12/2022
Page n. 4/ 1/3
Replaced revision:3 (Dated 22/10/2020)

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

				Calcium	dihydroxide				
Threshold Limit V	'alue								
Туре	Country	TWA/8h		STEL/15	min	Remarks / C	bservations		
		mg/m3	ppm	mg/m3	ppm				
MAK	DEU	1		2		INHAL			
VLA	ESP	1		4					
VLEP	FRA	1		4					
VLEP	ITA	1		4		RESP			
NDS/NDSCh	POL	2		6		INHAL			
NDS/NDSCh	POL	1		4		RESP			
WEL	GBR	5				INHAL			
WEL	GBR	1		4		RESP			
OEL	EU	1		4		RESP			
TLV-ACGIH		5							
Predicted no-effe	ct concentra	tion - PNEC							
Normal value in	fresh water						0,49	mg/l	
Normal value in	marine wate	er					0,32	mg/l	
Normal value for	r water, inter	mittent relea	se				0,49	mg/l	
Normal value of	STP microo	rganisms					3	mg/l	
Normal value for	r the terrestr	ial compartm	ent				1080	mg/kg	
Health - Derived r	o-effect leve	el - DNEL / D	DMEL						
Effects on consumers					Effects on wor	rkers			
Route of expos	ure Acut	te Acu	te	Chronic	Chronic	Acute	Acute	Chronic	Chronic
•	loca	l syst	emic	local	systemic	local	systemic	local	systemic
Inhalation	4	,		1	•	4	•	1	•
	mg/r	m3		mg/m3		mg/m3		mg/m3	



Revision nr.4 Dated 12/12/2022 Printed on 14/12/2022 Page n. 5 / 13 Replaced revision:3 (Dated 22/10/2020)

SECTION 8. Exposure controls/personal protection .../

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one[EC no. 24	47-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.
220-239-61 (3:1)	

Predicted no-effect concentration - PNEC		
Normal value in fresh water	3,39	μg/l
Normal value in marine water	3,39	μg/l
Normal value for fresh water sediment	27	μg/kg
Normal value for marine water sediment	27	μg/kg
Normal value of STP microorganisms	230	μg/l

Health - Derived	no-effect level - DNEL	/ DMEL

Effects on consumers				Effects on workers			
Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
local	systemic	local	systemic	local	systemic	local	systemic
	110		90				
	μg/kg bw/d		μg/kg bw/d				
40	NPI	20	NPI	40	NPI	20	NPI
μg/m3		μg/m3		μg/m3		μg/m3	
	NPI	NPI	NPI		NPI	NPI	NPI
	Effects on Acute local	Acute Acute local systemic 110 μg/kg bw/d 40 NPI μg/m3 NPI	Effects on consumers	Effects on consumers Acute Acute Chronic Chronic local systemic local systemic 110 90 µg/kg bw/d 40 NPI 20 NPI µg/m3 µg/m3	Effects on consumers Effects on ward Acute Acute Chronic Chronic Acute local systemic local systemic local 110 90 µg/kg bw/d µg/kg bw/d 40 NPI 20 NPI 40	Effects on consumers Effects on workers Acute Acute Chronic Acute Acute local systemic local systemic 110 90 µg/kg bw/d 40 NPI 20 NPI 40 NPI µg/m3 µg/m3 µg/m3 NPI µg/m3	Effects on consumers Effects on workers Acute Acute Chronic Acute Acute Chronic local systemic local systemic local 110 90 μg/kg bw/d μg/kg bw/d 40 NPI 20 NPI 40 NPI 20 μg/m3 μg/m3 μg/m3 μg/m3 μg/m3

			1,2-benziso	thiazol-3(2H)-	one			
Predicted no-effect cor	ncentration	- PNEC						
Normal value in fresh	water					4,03	μg/l	
Normal value in mari	ne water					403	ng/l	
Normal value for fres	Normal value for fresh water sediment					49,9	μg/kg	
Normal value for mar	Normal value for marine water sediment					4,99	μg/kg	
Normal value of STP	microorgani	isms				1,03	mg/l	
Health - Derived no-eff	ect level - D	NEL / DMEL						
	Effects on consumers					Effects on workers		
Pouto of exposure	Aguto	Acuto	Chronio	Chronio	Aguto	Acuto	Chronio	Chronio

	Effects or	n consumers			Effects on workers			
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation				1,2				6,81
				mg/m3				mg/m3
Skin				345				966
				μg/kg bw/d				μg/kg
								bw/d

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.





Revision nr.4 Dated 12/12/2022 Printed on 14/12/2022 Page n. 6 / 13 Replaced revision:3 (Dated 22/10/2020)

SECTION 8. Exposure controls/personal protection

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

> °C not applicable

not available 12,5-13,5

not available

not available

not available

not available

not applicable

1,65

Mixable in water

tixotropico

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Value Appearance pasty liquid Colour white Odour Hydraulic binder Melting point / freezing point not available Initial boiling point 100 Flammability not flammable Lower explosive limit not applicable Upper explosive limit not applicable

Flash point Auto-ignition temperature Decomposition temperature

Kinematic viscosity Dynamic viscosity Solubility

Partition coefficient: n-octanol/water Vapour pressure

Density and/or relative density Relative vapour density Particle characteristics

Information

q/litre

g/litre

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC): 0,37 % - 6,07 VOC (volatile carbon) 0,03 % - 0,53 Explosive properties not applicable

Oxidising properties not applicable

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

@EPY 11.4.1 - SDS 1004.14



Revision nr.4 Dated 12/12/2022 Printed on 14/12/2022
Page n. 7 / 13
Replaced revision:3 (Dated 22/10/2020)

.../>> **SECTION 10. Stability and reactivity**

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Calcium dihydroxide

ABSORPTION

The primary effect of calcium diidide on health is local irritation caused by pH variation. Therefore, absorption is not a relevant parameter for the assessment of the effects of the substance.

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)

ATE (Oral) of the mixture: >2000 mg/kg

ATE (Dermal) of the mixture: Not classified (no significant component)

Calcium dihydroxide

LD50 (Dermal): > 2500 mg/kg Rabbit (OCSE 402) LD50 (Oral): > 2000 mg/kg Rat (OECD 425)

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one[EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]

(3:1)

LD50 (Dermal): 1008 mg/kg bw (rat)

STA (Dermal): 50,001 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

LD50 (Oral): > 64 mg/kg bw 64-561 (rat) LC50 (Inhalation vapours): > 171 mg/m3 171-2360 (rat)

1.2-benzisothiazol-3(2H)-one

LD50 (Dermal): 2000 mg/kg bw (rat)

> 490 mg/kg bw 490-670 (rat) LD50 (Oral):

C12-C15 propoxylated alcohol

LD50 (Oral): > 2000 mg/kg Rat

STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

SKIN CORROSION / IRRITATION

Causes skin irritation

Calcium dihydroxide Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION



Revision nr.4 Dated 12/12/2022 Printed on 14/12/2022 Page n. 8 / 13 Replaced revision:3 (Dated 22/10/2020)

SECTION 11. Toxicological information .../>>

Causes serious eye damage

Calcium dihydroxide Causes severe eye injury

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) 1,2-benzisothiazol-3(2H)-one

Calcium dihydroxide

Does not meet the classification criteria for this danger class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

Calcium dihydroxide

Reverse Bacterial Mutation Essay (Ames Test, OECD 471): Negative

Testing chromosomal aberrations on mammal cells: negative

Given that calcium is an omnipresene and essential element and that any variation of the lime-induced pH in watery means has no relevance, calcium dihydroxide is ovially devoidant of any genotoxic potential. Classification by function of genotoxicity is not justified.

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Calcium dihydroxide

Calcium (administered in the form of lactate) is not carcinogenic (experimental result, rat). The effect on pH on the product of calcium diid dioxide is free of any carcinogenic potential. classification on the basis of carcinogenicity is not justified.

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Calcium dihydroxide

Calcium (administered in the form of Ca carbonate) is not toxic for reproduction (experimental result, mouse). The effect on pH does not give rise to any reproductive risk. Human epidemiological data confirm that calcium diid dioxide is free of any potential toxicity. In both animal and clinical trials on different calcium salts, no effect has been identified on reproductive and developmental toxicity. v. also the Scientific Committee of Human Food (Anonymous, 2006). Therefore, calcium diidide is not toxic for reproduction and/or development.

Classification on the basis of reproductive toxicity according to Regulation 1272/2008 is not necessary.

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

Calcium dihydroxide
It can irritate the airways

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Calcium dihydroxide

The toxicity of calcium through the oral exposure pathway is demonstrated by the increase in maximum tolerable intake levels (UL) for adults determined by the Scientific Committee of Human Food (SCF), where UL-2500 mg/die, equal to 38 mg/kg of weight/die, equal to 38 mg/kg of weight/die (individual weighing 70 kg) for calcium.

The toxicity of Ca(OH)2 through contact with the skin is not considered relevant by virtue of the expected insignificant absorption through the skin and the fact that local irritation is the primary effect for health (pH variation).

The toxicity of Ca(OH)2 by inhalation (local effect, mucous irritation), taking into account an average time weighed for an 8-hour shift, was determined by the Scientific Committee for Occupational Exposure Limits (SCOEL) in 1 mg/m3 of breathable dust. Therefore, the classification of Ca(OH)2 on the basis of toxicity as a result of prolonged exposure is not necessarily





Revision nr.4 Dated 12/12/2022 Printed on 14/12/2022 Page n. 9 / 13 Replaced revision:3 (Dated 22/10/2020)

SECTION 11. Toxicological information .../>>

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

Calcium dihydroxide

Does not meet the classification criteria for this danger class

Calcium diidhydroxide is classified as irritating to the skin and airways, and carries the risk of serious eye injury. The limit of occupational exposure for the prevention of sensory irritation at the local level and the reduction of lung function parameters as effects is OEL (8 hours) - 1 mg/m3 of breathable dust.

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Calcium dihydroxide

LC50 (96h) on sea fish: 457 mg/l

LC50 (96h) on sea invertebrates: 158 mg/l NOEC (72 hours) on freshwater algae: 48 mg/l TOXICITY ON MICROORGANISMS, ES BACTERIA

At high concentration, through temperature and pH rise, calcium diidhydxide is used for disinfection of sewer sludge.

NOEC (14 days) for sea invertebrates: 32 mg/l

EC10/LC10 or NOEC on soil macro-organisms: 2000 mg/kg soil dw EC10/LC10 or NOEC on soil microorganisms: 12000 mg/kg soil dw

NOEC (21 days) on terrestrial plants: 1080 mg/kg

GENERAL EFFECT

Acute effect of pH. Although this substance is useful for correcting water acidity, excess over 1 g/l can be harmful to aquatic organisms. A value of pH> 12 will decrease rapidly and as a result of dilution and carbonation.

Calcium dihydroxide

LC50 - for Fish 50,6 mg/l/96h freshwater fish EC50 - for Crustacea 49,1 mg/l/48h invertebrate EC50 - for Algae / Aquatic Plants 184,57 mg/l/72h alga

 $Reaction\ mass\ of\ 5-chloro-2-methyl-2H-isothiazol-3-one\ [EC\ no.\ 247-500-7]\ and\ 2-methyl-2H-isothiazol-3-one\ [EC\ no.\ 220-239-6]\ (3:1)$

LC50 - for Fish > 190 μg/l 190-330 EC50 - for Crustacea > 7 μg/l 7-160 EC50 - for Algae / Aquatic Plants > 6,3 μg/l 6,3-27,3 Chronic NOEC for Fish 46,4 μg/l 35 days Chronic NOEC for Crustacea > 111 μg/l 11.1-1050

1,2-benzisothiazol-3(2H)-one

LC50 - for Fish > 2,15 mg/l 2,15-22 EC50 - for Crustacea > 2,9 mg/l 2,9-2,94 EC50 - for Algae / Aquatic Plants > 70 μg/l 70-150 Chronic NOEC for Algae / Aquatic Plants > 40,3 μg/l 40-55

C12-C15 propoxylated alcohol

LC50 - for Fish > 100 mg/l/96h Pimephales promelas EC50 - for Crustacea > 100 mg/l/48h Daphnia pulex

EC50 - for Algae / Aquatic Plants > 100 mg/l/72h Selenastrum capricornutum

12.2. Persistence and degradability



Revision nr.4 Dated 12/12/2022 Printed on 14/12/2022 Page n. 10 / 13 Replaced revision:3 (Dated 22/10/2020)

SECTION 12. Ecological information .../>>

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one[EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Rapidly degradable

1,2-benzisothiazol-3(2H)-one Rapidly degradable

C12-C15 propoxylated alcohol NOT rapidly degradable

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Calcium dihydroxide

Calcium diidhydroxide is a moderately soluble substance and therefore has poor mobility in most soils.

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0.1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable





Revision nr.4 Dated 12/12/2022 Printed on 14/12/2022 Page n. 11 / 13 Replaced revision:3 (Dated 22/10/2020)

SECTION 14. Transport information .../>>

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC):

Decorative effect coatings.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances Calcium dihydroxide

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 1
Acute toxicity, category 1
Acute Tox. 2
Acute toxicity, category 2
Acute Tox. 3
Acute toxicity, category 3
Acute Tox. 4
Skin Corr. 1B
Eye Dam. 1
Skin Irrit. 2
Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin Sens. 1 Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

ΕN



OIKOS S.P.A. A SOCIO UNICO CEMENTO MATERICO

Revision nr.4 Dated 12/12/2022 Printed on 14/12/2022 Page n. 12 / 13 Replaced revision:3 (Dated 22/10/2020)

SECTION 16. Other information .../>>

H330 Fatal if inhaled.
H310 Fatal in contact with skin.
H330 Fatal if inhaled.
H301 Toxic if swallowed.
H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
H315 Causes skin irritation.

H335 May cause respiratory irritation.H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)

EPY 11.4.1 - SDS 1004.14



Revision nr.4 Dated 12/12/2022 Printed on 14/12/2022 Page n. 13 / 13 Replaced revision:3 (Dated 22/10/2020)

SECTION 16. Other information .../>>

- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 09 / 11 / 12 / 15 / 16.